CHAMPION SUPER NOP

54 OZ. NEEDLEPUNCHED CONTACT CARPET TILE

Timeless style, and incredible flexibility: Champion Super Nop is perfect for any application

Our most popular logo mat material is not only available in roll goods but tiles too! Featuring warm neutrals, fashionable brights and classic standard colors. Champion Super Nop Tile is our highest quality product that truly has something for everyone.

- *Highest quality needlepunched construction*
- *Solution-dyed, UV stabilized ASOTA® polypropylene fiber*
- *Incredible flexibility and unwavering performance*



1. Sterling 2344
2. Gris/ Charcoal 2098
3. Steel Blue 5157
4. Azure 5181
5. Midnight Blue 5154
6. Prism 5155
7. Hunter Green 6022
8. Verde Green 6043
9. Black Shadow 2343
10. Taupe 2345
11. Natural Beige 1153
12. Autumn 2048
13. Coir/ Natural 1099
14. Zinc 7006
15. Walnut 7068
16. Teak 7185
17. Loden 6081
18. Chocolate 7097
19. Rosewood 7178
20. Cardinal Red 3353
21. Garnet 3138

CHAMPION SUPER NOP CONTRACT CARPET TILE | DIVISION 9 | ZONES 2 & 3

CHAMPION SUPER NOP

54 OZ. NEEDLEPUNCHED CONTRACT CARPET TILE

2·3 ZONES | INDOOR

SUGGESTED USES (Not limited to)

Office Environments, Airports, Conference Rooms, Lobbies, Libraries, Retail/ Department Stores, Resorts, Restaurant Entryways, Spas, etc.

Construction:	Nonwoven/Needlepunched
Surface Aspect:	Hobnail (Berber) pattern
Primary Backing:	Premium (eco) Bitumen
Pile Height (± 0.5mm):	0.25"
Total Height (± 7.5%):	0.47"
Pile Weight (± 7.5%):	54 oz./sy
Total Weight (± 7.5%):	169 oz./sy
Tile Size (± 2%):	19.69" x 19.69"
Packaging:	12 tiles per box (32.5 sq. ft.)

LIMITED WARRANTY

Full Commercial Warranty 5 years

Summary of Warranty:

van Gelder, Inc. warrants Carpet Tiles against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to van Gelder, Inc. within the Warranty period, van Gelder, Inc. will supply new material of same or similar grade to repair or replace the defective material.

Wear:

Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 1 year from date of purchase, van Gelder, Inc. will provide replacement materials or repair, of only the effected area.

Manufacturing Defects:

van Gelder, Inc. warrants Carpet Tiles materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to five [5] years from date of purchase. van Gelder, Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

Other Limitations:

- This warranty is non-transferable.
- Manufacturing defect must be reported within 3 months from date of purchase.
- This Warranty covers only properly installed & maintained floors.
- van Gelder, Inc. excluded and will not pay for any consequential or incidental expenses.
- van Gelder, Inc. reserves the right of final judgment and may refuse claims in certain instances.

**For a copy of the full warranty please ask for a warranty sheet.*

PACKAGING & DIMENSIONS

Tiles (19.69" x 19.69" ea.): 12 tiles per box (32.5 sq. ft.)

ELECTROSTATIC SPECIFICATIONS

Dimensional Stability (ASTM D7570-09):	Pass
Electrostatic Propensity (EN 1815):	>2kV
Electrical Resistivity (IBM / ICL):	Pass, for R.H. ≥40%
Sound Insulation (ISO 10140-1:2010):	≥24dB
Thermal Retention (ISO 11092):	0.13 m K/W Pass

COLOR FASTNESS

To Light (ISO 105 B02):	5
To Water (ISO 105 E01):	5
To Shampoo (ISO 105 C06):	5
To Rubbing (ISO 105 X12):	4 (Dry), 3-4 (Wet)

FLAMMABILITY

Radiant Panel (ASTM E648 / DIN 4102):	Class II
Smoke Density (ASTM E662):	Pass
Surface Flammability (FF 1-70 / ASTM D2859):	Pass

LEED-NC **MR CREDIT 4 | IEQ CREDITS 4.1, 4.3, 5**

INSTALLATION (Tile)

Before laying tiles, it is recommended they are stored at room temperature 60°F-70°F (15°C-20°C). The tiles can be loose laid on flat, dry floors free from impurities such as oil, grease etc. Cracked floors should be filled, and uneven floors covered with hardboard. Dusty floors should be primed. Because of the high insulation value of these tiles it is not recommended they be laid when under-floor heating systems are in use. On very large installations, it is advisable to secure 1 in 5 rows with double-sided tape. Where tiles are to be used under caster chairs, tiles should be fully secured. The tiles may be laid by marking across in the center of the room and working outwards from this, the marker cross may be moved to facilitate the use of full tiles in doorways, etc. Tiles must be laid by turning alternate tiles through 90 degrees to obtain a checker pattern. An arrow on the back of each tile indicates the pile direction. Only tiles with the same batch number should be laid together.

For installation and other information, go to www.vangelder-inc.com.

MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.

Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

EXPERIENCE IT FOR YOURSELF

Talk with your sales representative or request samples at samples@vangelder-inc.com

YOUR AUTHORIZED SALES REPRESENTATIVE:

vG_CSN_CT_ISS_101722

van Gelder, Inc.
www.vangelder-inc.com
+1 866 284 6287

vG incorporated